



WINTECHNO MAT

Article Code see DDT

Date of issue 12.05.2011

Revision nr. 01

Page 1 of 2

Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italia Tel. +39 02/267.00.605 – Fax +39 02/267.00.621 –
info@winklerchimica.com www.winklerchimica.com

DESCRIPTION

Reinforcement for liquid waterproofing membrane. 100% special polyester fibers fabric.

Non-allergenic

Rot-proof

Resistant to atmospheric agents

Easy-fitting to every kind of surface

USES

WINTECHNO MAT is an ideal reinforcement for liquid waterproofs. Thanks to its flexibility it assures a great adaptation to the treated surfaces while for its extreme permeability it goes together well with the waterproofing liquid. Its versatility and the small thickness make WINTECHNO MAT an effective instrument even in case of existing floors, where following height differences, particularly near doorsteps, is extremely binding.

On old floors, often without waterproofing covering, we can directly proceed with the collocation of the new floor without removing the existent.

APPLICATION

1. Apply on the surface a small thickness of waterproof.
2. Lay WINTECHNO MAT and drown it by using a spatula.
3. Apply the second hand of waterproof.

TECHNICAL SHEET

WINTECHNO MAT			U.M
Weight	ISO 9073 - 1	50	g/m ²
Thickness	ISO 9073 - 1	0,45	mm
Breaking load	L T EN 12311 - 1	250 50	N/5 cm
Breaking elongation	L T EN 12311 - 1	15 30	%

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline. If at all in doubt, preliminary tests should be carried out. WINKLER S.r.l. reserves the right to modify and up-date said data sheets without prior notice. Clients are kindly requested to verify that they are in possession of the current edition.



WINTECHNO MAT

Article Code see DDT

Date of issue 12.05.2011

Revision nr. 01

Page 2 of 2

Via M. Buonarroti, 15 – 20093 Cologno M.se (MI) – Italia Tel. +39 02/267.00.605 – Fax +39 02/267.00.621 –
info@winklerchimica.com www.winklerchimica.com

SUPPLY DATA

	WIN TECHNO MAT	U.M.
Height	100	cm
Lenght	200	m
Development	200	m ²
Quantity per pallet	9 1800	rolls m ²

SAFETY INSTRUCTIONS

PRECAUTIONS

For information about safety, user must refer to the most recent Safety Data Sheet, edited in accordance with the regulations in force, which contains physical, toxic and other data about the product in use.

ECOLOGY

Do not through out the product and/or empty containers in the environment. Consult the most recent Safety Data Sheet for further information about disposals.

The information contained in this technical data sheet is to the best of our knowledge correct. However, by no means can it be considered a guarantee, as usage, working area and application of the product in accordance with the instructions given and their success in application is beyond our control and is dependent on a number of factors. We decline any responsibility for the improper use of the product as the application recommendations contained herein are to be considered as a general guideline. If at all in doubt, preliminary tests should be carried out. WINKLER S.r.l. reserves the right to modify and up-date said data sheets without prior notice. Clients are kindly requested to verify that they are in possession of the current edition.